

# WellH<sup>o</sup>se<sup>®</sup>

## DIY Drop Pipe

### Specifications

NORMAL SIZE	1"	1.25"	1.5"	2"	2.5"	3"	4"
DIAMETER OF WELLHOSE	25 mm	32 mm	40 mm	50 mm	65 mm	76 mm	102 mm
MAX DEPTH SETTING	300 ft 90 m	300 ft 90 m	250 ft 75 m	200 ft 60 m	200 ft 60 m	150 ft 45 m	150 ft 45 m
WEIGHT OF WELLHOSE	0.14 lb/ft 0.20 kg/m	0.17 lb/ft 0.26 kg/m	0.20 lb/ft 0.32 kg/m	0.34 lb/ft 0.53 kg/m	0.53 lb/ft 0.82 kg/m	0.60 lb/ft 0.94 kg/m	0.86 lb/ft 1.35 kg/m
WEIGHT OF WATER	0.4 lb/ft 0.6 kg/m	0.9 lb/ft 1.3 kg/m	1.4 lb/ft 2.0 kg/m	1.6 lb/ft 3.0 kg/m	2.6 lb/ft 4.0 kg/m	3.5 lb/ft 6.0 kg/m	6.2 lb/ft 10 kg/m
TORQUE SETTINGS	5 Nm 4 ft.lb	7 Nm 5 ft.lb	7 Nm 5 ft.lb	11 Nm 8 ft.lb	14 Nm 10 ft.lb	16 Nm 12 ft.lb	20 Nm 15 ft.lb

*This product is not for use with contaminated water without prior written approval.*

With **WELLHOSE DIY Drop Pipe** you can really Do It Yourself.

# WellHose®

## DIY Drop Pipe

- Easy to install and retrieve your own pump
- Cut to suit your exact pump setting
- Ideal for domestic or remote areas
- 10 Year Manufacturer Warranty
- Great in all weather conditions
- Available as a Plug and Play package



**WELLHOSE DIY Drop Pipe** makes your life easy. Available as a plug and play with submersible pump and power cable pre-attached. All you have to do is lower it into the well.

**Supplied By:**

Sales@HoseSolutions.com  
HoseSolutions.com

9419 E. San Salvador Drive #104  
Scottsdale, AZ 85258 USA  
+1 (480) 607-1507

HoseSolutions Inc

Ref: 060122